

| Mini Reclamation System System A 500-1500 PPH Basic Systems Equipment | System A / MRS 500 - 1,500 lb/hr (225 - 680 kg/hr) |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| Ave. Production Rate (55% Cu content) | 850 lb/hr (386 kg/hr) |
| Annual Production (1700 hours per shift) One Shift | 1,445,000 lbs (656,200 kgs) |
| Two Shifts | 2,890,000 lbs (1,312,400 kgs) |
| Recommended minimum building size | skid size: 6.7W x 18.5L x 7.5H, use space: 21W x 18.5L x 12H |
| Approximate connected power | 110 HP (82 kW) |
| Primary Granulator | 24 Husky |
| Feedrolls | None |
| Primary Magnet | Optional |
| Secondary Granulator | None |
| Tertiary Granulator | None |
| High Speed Screen | 3' x 6' Opt. |
| Fines Aspirator | None |
| Bins | Dual surge bin option |
| Fluidized Bed Separator | BX-110 |
| Stoner (Option only) | S-22H |
| Fans & Cyclone | 5,000 cfm |
| Vibrating Conveyors | 2 |
| Belt Conveyors | 1 |
| Elevators | 2 |